

BUNDLING MACHINE MS 90 AL

**SEMI-AUTOMATIC SLEEVE WRAPPER WITH DOUBLE
MOTORISED BELT - INCORPORATED TUNNEL - SEALING BAR
900 MM**

semiautomatic or automatic with motorised belt before and after sealing bar



DESCRIPTION

The new series of **Minipack-Torre** bundling machines is characterised by the great versatility of the models combining efficiency, reliability and high performance. This all guarantees ideal working conditions in any situation the user carries out the activity.

The models of the MS L and AL range represent the best solution for incorporating the machine in production lines, as they are all set up for automatic management of the line infeed and outfeed exchange signals.

The MS L and AL Bundling Machines wrap both individual and multiple products in polyethylene film. They can wrap products as long as 1500 mm. Thanks to the control selector, the operator can choose whether to work in automatic or semiautomatic mode.

TECHNICAL FEATURES

| | | |
|---------------------------|-----------|--------------------------------|
| Power supply | V | 220/400 |
| Phase | ph | 3 |
| Electric Power | kW | 27 |
| Electric consumption | kWh | 14 |
| Air Pressure | bar | 6 |
| Air Consumption per cycle | nl | 10 |
| Hourly production | p/h (pph) | Up to 10 ppm |
| Sealing Bar | mm | 900 |
| MAX product height | mm | 380 (can be changed on demand) |
| MAX reel dimensions | mm | Ø 350x880 |
| Worktop height | mm | Standard 850+25 |
| Machine dimensions | mm | 3900x1500x h.1980 |
| Tunnel infeed dimensions | mm | 800x h.400 |
| Tunnel chamber length | mm | 1500 |
| Machine weight | kg | 1250 |

minipack®-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.