

# MINIFLOW 400

## COMPLETELY ELECTRIC FLOW-PACK

Ideal for baked goods, pharmaceuticals and various objects.



## DESCRIPTION

---

The **Miniflow 400** is the new “Flow-Pack” packaging machine by **Minipack-Torre**. Designed to simplify maintenance and cleaning operations for the customer as much as possible.

Thanks to the **3 high-performance Brushless** motors and its **7” Touch-Screen panel**, it will guarantee maximum versatility with format changes and therefore extreme simplicity in packaging operations.

It can package strapped products, **max 180 mm**, and can reach **100 packages per minute**. With an optimal quality/price ratio, this packaging machine combines quality and technology, and it guarantees a high level of reliability.

This machine is suitable for packaging: Brioche, sweets, pharmaceutical products, sweets, chocolates, chocolate, various small objects and much more.

The Miniflow 400 packaging machine can be equipped with many optional features.

## TECHNICAL FEATURES

Power supply	V	220
Pneumatic supply	Bar	6
Phase	ph	1
Electrical power	kW	2.5
Electric consumption	kWh	2.3
Hourly production	p/h (pph)	Up to 6,000
Sealing Bar	mm	190
MAX product weight	g	500
MAX product height	mm	75
MAX product length	mm	500
Reel Diameter MAX Dimensions	mm	350
MAX Reel Strip Dimensions	mm	420
Worktop height	mm	800/950
Machine dimensions	mm	2400x800x h.1800
Machine weight	V	220

minipack®-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.

## CHARACTERISTICS:

---

- User-friendly 7" PLC touch screen
- Easy inspection for maintenance and cleaning of roller
- unit Expandable pneumatic shaft for film support 3
- brushless motors
- Photocell to centre printed film
- 2 pairs of infeed rollers
- Safety housing, with stoppage system in the event of opening
- EC certified safety and management modules
- Motorised product unloading belt with central guide
- Emergency button with immediate interruption of the production
- cycle Inspectable magnetic roller bars
- Sliding surface in AISI 304 stainless steel conforming with EC regulations
- "Crumb catcher" boxes on the infeed belt Rotating collectors
- with integrated brushes
- Parameter and recipe backup via USB port
- Belt handling mechanism to reduce play
- Network connection for assistance via LAN and VNC L cable